

AD610712

# DETECTION OF A PATTERN IN UNKNOWN POSITION

C. K. Rushforth

Electro-Dynamics Laboratories  
UTAH STATE UNIVERSITY  
Logan, Utah




COPY	2	OF	3	24
HARD COPY			\$ .200	
MICROFICHE			\$ .050	

29P

SCIENTIFIC REPORT NO. 2  
Contract No. AF 19(628)-3825  
1 November, 1964

Sponsored by  
ARPA Order No. 450  
Project No. 8663

Prepared for  
AIR FORCE CAMBRIDGE RESEARCH LABORATORIES  
OFFICE OF AEROSPACE RESEARCH  
UNITED STATES AIR FORCE  
Bedford, Massachusetts



ARCHIVE COPY

**BEST  
AVAILABLE COPY**

## **NOTICES**

**Requests for additional copies by Agencies of the Department of Defense, their contractors, and other Government agencies, should be directed to:**

**DEFENSE DOCUMENTATION CENTER (DDC)  
CAMERON STATION  
ALEXANDRIA, VIRGINIA 22314**

**Department of Defense contractors must be established for DDC clearance or have their "need-to-know" certified by the cognizant military agency of their project or contract.**

**All other persons and organizations should apply to:**

**U. S. DEPARTMENT OF COMMERCE  
OFFICE OF TECHNICAL SERVICES  
WASHINGTON 25, D. C. 20230**

AFCRL-64-1011

DETECTION OF A PATTERN IN UNKNOWN POSITION

C. K. Rushforth

Electro-Dynamics Laboratories  
UTAH STATE UNIVERSITY  
Logan, Utah

SCIENTIFIC REPORT NO. 2  
Contract No. AF19(628)-3325  
1 November 1964

Sponsored by  
ARPA Order No. 450  
Project No. 3663

Prepared for  
Air Force Cambridge Research Laboratories  
Office of Aerospace Research  
UNITED STATES AIR FORCE  
Bedford, Massachusetts

## ABSTRACT

In this paper, the problem of detecting an optical pattern in unknown position is considered. Two detection procedures are investigated--one which entails a search procedure, and one which does not. The false-alarm and false-dismissal probabilities for these two procedures are evaluated under certain simplifying assumptions in order to compare the two procedures with each other and with the detector which is optimum when the position of the pattern is known. It is shown that there is a trade-off between error rate and information rate. The procedure requiring a search technique processes the data less rapidly, but at the same time achieves a lower error rate for a given signal-to-noise ratio. This analysis also applies to the problem of detecting a signal with unknown arrival time provided that the assumptions stated herein are satisfied.

## TABLE OF CONTENTS

INTRODUCTION . . . . .	1
DETECTION OF A KNOWN PATTERN . . . . .	3
DETECTION OF A SIGNAL IN UNKNOWN POSITION-- SEARCH TECHNIQUE . . . . .	5
DETECTION OF A SIGNAL IN UNKNOWN POSITION WITHOUT SEARCH . . . . .	9
CONCLUSIONS . . . . .	16
REFERENCES . . . . .	21
ACKNOWLEDGEMENTS . . . . .	22

## INTRODUCTION

An important problem in optical data processing is that of determining whether or not a particular pattern is present in the image plane of an optical system. Various versions of this problem obtain depending on the prior knowledge available about the pattern to be detected and the noise in the system. The methods of statistical decision theory [1] can be used to derive optimum detection procedures which depend on this prior information and on the costs of the different types of errors.

In this paper we first review briefly some known results pertaining to the detection of a pattern which is exactly known in the presence of additive white Gaussian noise. We then relax the assumption that the position of the pattern in the image plane is known while retaining the assumption that its shape is known. Two detection procedures for this modified problem are considered, one which entails searching for the pattern and one which does not. Under certain simplifying assumptions, the false-alarm and false-dismissal probabilities are evaluated as functions of signal-to-noise ratio for each of these procedures. These probabilities are compared with each other and with the false-alarm

and false-dismissal probabilities obtained using the optimum detector when the signal position is known. It is shown that there is a trade-off between information rate and error rate. If the procedure requiring search is used, it takes longer to process the data, but at the same time the error rate is reduced. The choice of a procedure will depend on the signal and noise parameters and on the performance required.



## DETECTION OF A KNOWN PATTERN

In this section, we briefly review some known results for the detection of a known signal or pattern. These results will be useful for purposes of comparison in later sections.

The problem we treat is the following: Let  $X(\xi, \eta)$  be the observed intensity distribution in the image plane, where  $\xi$  and  $\eta$  are the image-plane coordinates. The object of the detector is to determine whether  $X(\xi, \eta)$  consists of noise alone ( $X = N$ ) or of signal plus noise ( $X = S + N$ ), where  $S(\xi, \eta)$  is exactly known to the detector.

By employing an appropriate sampling procedure [2, 3], we can represent the functions  $X(\xi, \eta)$ ,  $N(\xi, \eta)$  and  $S(\xi, \eta)$  by the finite-dimensional vectors  $\underline{X} = \begin{pmatrix} x_1 \\ \vdots \\ x_m \end{pmatrix}$ ,  $\underline{N} = \begin{pmatrix} n_1 \\ \vdots \\ n_m \end{pmatrix}$ , and  $\underline{S} = \begin{pmatrix} s_1 \\ \vdots \\ s_m \end{pmatrix}$

The noise samples  $n_1 \dots n_m$  are assumed to be independent Gaussian random variables with mean zero and variance one.

It has been shown [4] that the optimum detector for this problem computes the quantity

$$L(\underline{X}) = \underline{X}' \underline{S} \tag{1}$$

where  $\underline{X}'$  is the transpose of  $\underline{X}$ , and compares it with a threshold. If

this threshold is exceeded, the pattern is said to be present. Otherwise, it is decided that noise alone is present. This is the well-known matched filter or correlation detector.

If  $\gamma$  is the threshold described above, the false-alarm and false-dismissal probabilities are

$$P(\text{FA}) = P[\underline{X}'\underline{S} > \gamma \mid \underline{N} \text{ alone}] \quad (2)$$

and

$$P(\text{FD}) = P[\underline{X}'\underline{S} < \gamma \mid \underline{S} + \underline{N}] \quad (3)$$

These probabilities are easy to evaluate in the present case [4]. Curves are plotted in Figures 1 - 4 for comparison with similar curves obtained when the position of the signal is not known.

## DETECTION OF A SIGNAL IN UNKNOWN POSITION-- SEARCH TECHNIQUE

In many applications, it is realistic to assume that the shape of the pattern to be detected is known, but that its exact position is not. In this paper, we assume that the orientation as well as the shape is known but allow an unknown translation. Any detection scheme for this situation will, of course, suffer a certain amount of degradation due to the additional noise which the position uncertainty allows to enter the system. Two questions occur in connection with this problem. First, how much degradation do various schemes suffer relative to the optimum known-position detector? Second, how do these schemes compare with one another? In this section and the next, we consider and compare two such schemes.

In optical data processing, the correlation detector or matched filter can take the form of a mask with the same shape as the pattern to be detected. The amount of light which passes through the mask is the quantity on which the decision is based. If the position of the pattern (if it is present) in the image plane is known, the mask is simply placed in that position and the transmitted light compared with the threshold.

If the position of the pattern is not known, the above detection procedure must be modified. The optimum procedure under certain reasonable assumptions about the prior knowledge is not difficult to obtain mathematically, but it is rather complicated to instrument and extremely difficult to evaluate. Hence, this optimum procedure is not considered in this paper. Instead, two reasonable sub-optimum detection procedures are considered and compared.

When the position of the pattern in the image plane is not known, a reasonable way to modify the matched-filter detection procedure is to move the mask around and compare successive outputs with threshold. If the output exceeds the threshold in any one position, say the pattern is present. Otherwise, say noise alone is present.

If the dimension of the signal vector is greater than one and if all possible signal positions are searched, there will be overlap in the matched-filter outputs. The random variables involved are then dependent, and evaluation of system performance becomes very complicated. The essential features of the problem are preserved, and performance evaluation is made tractable, if it is assumed that the signal vector consists of just one non-zero sample. The output random variables in different positions will then be independent, and the false-alarm and false-dismissal probabilities can be evaluated quite easily.

To be more specific, we consider the following problem. A vector  $\underline{X} = \begin{pmatrix} x_1 \\ \vdots \\ x_m \end{pmatrix}$  is presented to a detector whose objective is to determine whether  $\underline{X}$  consists of noise alone or of signal plus noise. If noise alone is present, we have  $x_i = n_i$  for all  $i = 1, \dots, m$ , where the  $n_i$  are independent Gaussian random variables with zero mean and unit variance. If signal is present, we have  $x_i = n_i$  for all  $i = 1, \dots, m$ , except  $i = j$ , and  $x_j = s + n_j$ .  $s$  is a known scalar, but  $j$  is not known. That is, the position of the signal in the image plane is not known.

The following detection scheme is used. Compare each  $x_i$  with a threshold  $\gamma$ . If all of the  $x_i$  are less than  $\gamma$ , choose noise alone; if at least one  $x_i > \gamma$ , choose signal plus noise. Note that this procedure is equivalent to moving the matched-filter mask around as described above, since matched filtering in this case corresponds to scalar multiplication.

The false-alarm and false-dismissal probabilities for this detection procedure are quite easy to evaluate. We have

$$\begin{aligned} P(\text{FA}) &= P \left\{ \text{at least one } x_i > \gamma \mid \text{noise alone} \right\} \\ &= 1 - P \left\{ \text{all } x_i \leq \gamma \mid \text{noise alone} \right\} \\ &= 1 - [P(n \leq \gamma)]^m \end{aligned} \tag{4}$$

where  $n$  is a Gaussian random variable with zero mean and unit variance. For a given  $m$ , the threshold  $\gamma$  can be chosen to yield any preassigned false-alarm probability.  $\gamma$  having thus been determined, the false-dismissal probability can then be calculated as a function of the signal strength  $s$  as follows.

$$\begin{aligned} P(\text{FD}) &= P \left\{ \text{all } x_i \leq \gamma \mid \underline{S} + \underline{N} \right\} \\ &= P(u \leq \gamma) [P(n < \gamma)]^{m-1} \end{aligned} \quad (5)$$

where  $n \sim N(0, 1)$  and  $u \sim N(s, 1)$ . This can also be written

$$P(\text{FD}) = P(n \leq \gamma - s) [P(n \leq \gamma)]^{m-1} \quad (6)$$

These probabilities can be easily evaluated using a table of the unit normal distribution function. Plots of  $P(\text{FD})$  as a function of  $s$  for  $P(\text{FA}) = .01$  and  $P(\text{FA}) = 0.1$  and various values of  $m$  are shown in Figures 1-4.

## DETECTION OF A SIGNAL IN UNKNOWN POSITION WITHOUT SEARCH

One disadvantage of the procedure described in the previous section is the time required to search for the signal. This reduces the rate at which data can be processed. It would be desirable to have available a method of detection which is independent of the exact position of the pattern and which does not entail a search procedure. One such method has been considered by Horwitz and Shelton [5]. This procedure is briefly described here, and its performance is evaluated for a special case and compared with those of the optimum known-position detector and the search procedure.

To motivate this detection procedure, consider a one-dimensional signal  $s(\xi - \xi_0)$ . Suppose that  $s(\xi)$  is an exactly-known signal having Fourier transform  $S(f)$  but that  $\xi_0$  is unknown. For any fixed  $\xi_0$ , the Fourier transform of  $s(\xi - \xi_0)$  is  $e^{-j\omega\xi_0} S(f)$ . Clearly, the square of the magnitude of this quantity, which is just the energy spectral density of the signal  $s(\xi - \xi_0)$ , is independent of the unknown position  $\xi_0$ . Hence, this energy spectrum can be used in various ways to detect a signal in unknown position.

In the detection procedure considered in [5], the detector simply cross-correlates the energy spectrum of  $s(\xi)$ ,  $|S(f)|^2$ , with the energy

spectrum of the observed waveform,  $|X(f)|^2$ . If the pattern is present,  $|X(f)|^2$  will consist of  $|S(f)|^2$  plus a noise term regardless of the position of the signal. Hence, this scheme is effective for essentially the same reasons that the ordinary correlation receiver is effective. The noise term is increased due to the uncertainty in position, however, and this noise is no longer Gaussian.

In order to evaluate this procedure, it is convenient to obtain an expression for the detector output in terms of autocorrelation functions rather than energy spectra. By Parseval's theorem, the output of the detector can be expressed as [5]

$$V = \sum_{i=-m+1}^{m-1} R_s(i) R_x(i) \quad (7)$$

where the discrete autocorrelation functions  $R_s(i)$  and  $R_x(i)$  are given by

$$R_s(i) = \sum_{j=1}^m s_j s_{i+j} \quad (8)$$

and

$$R_x(i) = \sum_{j=1}^m x_j x_{i+j} \quad (9)$$

The detector output can be expressed as a quadratic form in the variables  $x_i$  as follows:



$$V = \sum_{i=-m+1}^{m-i} R_s(i) \sum_{j=1}^m x_j x_{i+j} \quad (10)$$

In matrix form,

$$V = \underline{X}' \underline{R} \underline{X} \quad (11)$$

where

$$\underline{R} = (r_{ij}), \quad r_{ij} = R_s(|i-j|) \quad (12)$$

Quadratic forms of this type in Gaussian random variables have been treated by Middleton [6]. Although the characteristic function can be found for a general quadratic form of this type, the probability density function can be found only for certain special cases. If  $m$  is large,  $V$  becomes approximately Gaussian, but it is dangerous to use this approximation to compute error probabilities. The approximation is at its worst in the tails of the distribution, and it is precisely in these tails that the information regarding error probability lies. Rather than resort to this questionable approximation, we consider a special case for which the probability density functions can be found exactly.

We assume that the signal  $\underline{S}$  is such that  $R_s(i)$  is zero or approximately zero for  $i \neq 0$ . This will be true in particular if  $\underline{S}$  consists

of a single signal sample. Since this is precisely the case for which the search procedure was evaluated, we will be able to compare the two procedures directly in similar circumstances.

With this as background, we now state explicitly the problem to be solved. Let  $X = \begin{pmatrix} x_1 \\ \vdots \\ x_m \end{pmatrix}$  be the observed vector. The purpose of the detector is to use this observation to determine whether or not a known scalar signal  $s$  is present. If noise alone is present,  $x_1, \dots, x_m$  are independent Gaussian random variables with mean zero and unit variance. If signal is present, one of the  $x_i$  is Gaussian with mean  $s$  and variance unity, and the rest, as before, are Gaussian with mean zero and unit variance. As in the case of noise alone, all the  $x_i$  are assumed to be independent.

The detector computes the quantity  $V = \underline{X}^t \underline{X}$  and compares it with a threshold  $\gamma$ . If  $V > \gamma$ , the pattern is said to be present. Otherwise, it is said to be absent. Hence

$$P(\text{FA}) = P\{V > \gamma \mid \underline{N}\} \quad (13)$$

$$P(\text{FD}) = P\{V \leq \gamma \mid \underline{S} + \underline{N}\} \quad (14)$$

In order to evaluate these probabilities, we must first obtain the conditional probability density functions  $f(V \mid \underline{N})$  and  $f(V \mid \underline{S} + \underline{N})$ .

When noise alone is present,  $V = \underline{X}'\underline{X} = x_1^2 + x_2^2 + \dots + x_m^2$  is just the sum of squares of  $m$  independent Gaussian random variables with zero mean and unit variance. Hence,  $V$  is a chi-square random variable with  $m$  degrees of freedom. The conditional PDF of  $V$  when noise alone is present is

$$f(V|\underline{N}) = \begin{cases} (V/2)^{(m/2)-1} \frac{e^{-V/2}}{2^{(m/2)}} , & V \geq 0 \\ 0 & , V < 0 \end{cases} \quad (15)$$

The false-alarm probability is

$$P(\text{FA}) = \int_{\gamma}^{\infty} f(V|\underline{N}) dV \quad (16)$$

a quantity which may be obtained from tables of the chi-square distribution [ 7]. As before, we choose  $\gamma$  such that  $P(\text{FA}) = .01$  and  $P(\text{FA}) = 0.1$  for various values of  $m$  and then plot  $P(\text{FD})$  as a function of signal strength for these values of  $\gamma$  and  $m$ .

When signal is present, the quadratic form  $V = \underline{X}'\underline{X}$  computed by the detector is a special case of a form treated by Middleton [ 6]. From his (17.32b) and problem 17.9, we see that in our notation the conditional characteristic function of  $V$  in the presence of signal plus noise is

$$\varphi(i\xi | \underline{S} + \underline{N}) = \frac{1}{(1-2i\xi)^{m/2}} \exp \left\{ \frac{i\xi s^2}{1-2i\xi} \right\} \quad (17)$$

The conditional probability density function  $f(V | \underline{S} + \underline{N})$  is obtained from  $\varphi(i\xi | \underline{S} + \underline{N})$  by taking the Fourier transform. This quantity can be obtained from pair 650.0 of Campbell and Foster [8] upon making the change of variable  $P = -2i\xi$ . This yields

$$f(V | \underline{S} + \underline{N}) = \begin{cases} \frac{1}{2} e^{-s^2/2} (V/s^2)^{(m-2)/4} e^{-V/2} I_{m/2-1}(\sqrt{Vs^2}), & V > 0 \\ 0, & V < 0 \end{cases} \quad (18)$$

Where  $I_v$  is a modified Bessel function of the first kind, order  $v$ .

The false-dismissal probability for this detection scheme is

$$\begin{aligned} P(\text{FD}) &= \int_{-\infty}^{\gamma} f(V | \underline{S} + \underline{N}) dV \\ &= \frac{1}{2} e^{-s^2/2} \int_0^{\gamma} (V/s^2)^{(m-2)/4} e^{-V/2} I_{m/2-1}(\sqrt{Vs^2}) dV \end{aligned} \quad (19)$$

Integrals of this type have been treated by Marcum and Swerling [9] in connection with radar detection. From (100b) of [9], we see that  $P(\text{FD})$  can be expressed in terms of the incomplete Toronto function.


In our notation,

$$P(\text{FD}) = T_{\sqrt{\gamma}/2}(m-1, m/2-1, s/\sqrt{2}) \quad (20)$$


Curves giving values of the incomplete Toronto function for various values of  $\gamma$ ,  $s$ , and  $m$  are contained in [9], Figures 13-32. Using these curves, we obtain  $P(\text{FD})$  as a function of signal strength for various values of  $m$  and for values of  $\gamma$  corresponding to  $P(\text{FA}) = 0.01$  and  $P(\text{FA}) = 0.1$ . These values of  $P(\text{FD})$  are plotted in Figures 1-4, along with corresponding values for the optimum known-position detector and the search detector.

## CONCLUSIONS


The essential conclusions are in agreement with intuition. Lack of position information inevitably leads to a higher error rate. Searching for the signal yields a lower information rate, but also a lower error rate, than a system which processes the information instantaneously. Figures 1-4 provide quantitative information regarding this trade-off.




**FIG. 1**









**FIG. 4**

## REFERENCES

- [1] D. Blackwell and M.A. Girshick, Theory of Games and Statistical Decisions, John Wiley and Sons, 1954.
- [2] C.E. Shannon, "Communication in the Presence of Noise," Proc. IRE, 37, 1949; pp. 10-21.
- [3] D.A. Linden, "A Discussion of Sampling Theorems," Proc. IRE, 47, 1959; pp. 1219-1226.
- [4] W. W. Harman, Principles of the Statistical Theory of Communication, McGraw-Hill, 1963.
- [5] L.P. Horwitz and G. L. Shelton, Jr., "Pattern Recognition using Autocorrelation," Proc. IRE, 49, 1961; pp. 185-195.
- [6] D. Middleton, Introduction to Statistical Communication Theory, McGraw-Hill, 1960.
- [7] E.S. Keeping, Introduction to Statistical Inference, Van Nostrand, 1960.
- [8] G.A. Campbell and R.M. Foster, Fourier Integrals for Practical Applications, Van Nostrand, 1948.
- [9] J.I. Marcum and P. Swerling, "Studies of Target Detection by Pulsed Radar," IRE Transactions on Information Theory, April, 1960.
- [10] L.A. Wainstein and V.D. Zubakov, Extraction of Signals from Noise, Prentice-Hall, 1962.

### ACKNOWLEDGEMENTS

This report was generated under Air Force Cambridge Research Laboratories Contract No. AF19(628)-3825. The contributions of Drs. George A. Vanasse, Contract Monitor, and Doran J. Baker, Joint Project Director, are acknowledged.

**BLANK PAGE**

UNCLASSIFIED

Security Classification

## DOCUMENT CONTROL DATA - R&amp;D

(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

1. ORIGINATING ACTIVITY (Corporate author)		2a. REPORT SECURITY CLASSIFICATION	
Utah State University Logan, Utah		Unclassified	
		2b. GROUP	
		Electro-Dynamics Labs	
3. REPORT TITLE			
Detection of a Pattern in Unknown Position			
4. DESCRIPTIVE NOTES (Type of report and inclusive dates)			
Scientific Report No. 2			
5. AUTHOR(S) (Last name, first name, initial)			
Rushforth, Craig K.			
6. REPORT DATE		7a. TOTAL NO. OF PAGES	7b. NO. OF REFS
1 November 1964		17	10
8a. CONTRACT OR GRANT NO.		9a. ORIGINATOR'S REPORT NUMBER(S)	
AF19(628)-3825			
b. PROJECT NO.			
8663			
c. TASK		9b. OTHER REPORT NO(S) (Any other numbers that may be assigned this report)	
d.		AFCRL-64-1011	
10. AVAILABILITY/LIMITATION NOTICES			
Requests for additional copies by Agencies of the Department of Defense, their contractors, and other Government agencies should be directed to Defense Documentation Center (DDC), Cameron Station, Virginia, 22314			
11. SUPPLEMENTARY NOTES		12. SPONSORING MILITARY ACTIVITY	
		AFCRL, OAR USAF L. G. Hanscom Field, Bedford, Mass.	
13. ABSTRACT			
<p>In this report the problem of detecting a pattern in unknown position is considered. Two detection procedures are investigated - one which entails a search procedure, and one which does not. The false alarm and false dismissal probabilities for these two procedures are evaluated under certain simplifying assumptions in order to compare the two procedures with each other and with the detector which is optimum when the position of the pattern is known. It is shown that there is a tradeoff between error rate and information rate. The procedure requiring a search technique processes the data less rapidly, but at the same time achieves a lower error rate for a given signal-to-noise ratio.</p>			

UNCLASSIFIED

Security Classification

14. KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT
Communication Theory Fourier Optics Pattern Recognition						

### INSTRUCTIONS

1. **ORIGINATING ACTIVITY:** Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (*corporate author*) issuing the report.

2a. **REPORT SECURITY CLASSIFICATION:** Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

2b. **GROUP:** Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

3. **REPORT TITLE:** Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.

4. **DESCRIPTIVE NOTES:** If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

5. **AUTHOR(S):** Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

6. **REPORT DATE:** Enter the date of the report as day, month, year, or month, year. If more than one date appears on the report, use date of publication.

7a. **TOTAL NUMBER OF PAGES:** The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

7b. **NUMBER OF REFERENCES:** Enter the total number of references cited in the report.

8a. **CONTRACT OR GRANT NUMBER:** If appropriate, enter the applicable number of the contract or grant under which the report was written.

8b, 8c, & 8d. **PROJECT NUMBER:** Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

9a. **ORIGINATOR'S REPORT NUMBER(S):** Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

9b. **OTHER REPORT NUMBER(S):** If the report has been assigned any other report numbers (*either by the originator or by the sponsor*), also enter this number(s).

10. **AVAILABILITY/LIMITATION NOTICES:** Enter any limitations on further dissemination of the report, other than those imposed by security classification, using standard statements such as:

- (1) "Qualified requesters may obtain copies of this report from DDC."
- (2) "Foreign announcement and dissemination of this report by DDC is not authorized."
- (3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through \_\_\_\_\_."
- (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through \_\_\_\_\_."
- (5) "All distribution of this report is controlled. Qualified DDC users shall request through \_\_\_\_\_."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. **SUPPLEMENTARY NOTES:** Use for additional explanatory notes.

12. **SPONSORING MILITARY ACTIVITY:** Enter the name of the departmental project office or laboratory sponsoring (*paying for*) the research and development. Include address.

13. **ABSTRACT:** Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U).

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. **KEY WORDS:** Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, rules, and weights is optional.